

ELVARME

VARMEKABLER



**VARMEKABEL
CAEX**

NEWTRONIC

CAEX



The series heating cable CAEx is usually wound around the outer side of pipes in order to prevent the formation of ice in pipes. The cable is equipped with a bimetal thermostat in the version $+3^{\circ}\text{C} \pm 3^{\circ}\text{C}$ $+8^{\circ}\text{C} \pm 3^{\circ}\text{C}$ (also available in the version $+3^{\circ}\text{C} \pm 3^{\circ}\text{C}$ $+13^{\circ}\text{C} \pm 3^{\circ}\text{C}$), which activates the circuit only when a specific temperature is reached, thus enabling significant energy savings. The cable is supplied cut to measure and with schuko plug to offer a practical plug-in solution: the cable length cannot be shortened by the end user.

GENERAL TECHNICAL FEATURES:

- Supply Voltage: 220/240V
- Power: 15W/m or 20W/m
- External diameter: $6.5\text{mm} \pm 0.5\text{mm}$
- Standard insulation materials available: according to drawing
- Minimum bending radius: 25mm
- Maximum operating temperatures: $+105^{\circ}\text{C}$
- Length of heating and cold parts customizable on request
- Thermostat operating temperatures: $+3^{\circ}\text{C} \pm 3^{\circ}\text{C}$ $+8^{\circ}\text{C} \pm 3^{\circ}\text{C}$ (also available in the version $+3^{\circ}\text{C} \pm 3^{\circ}\text{C}$ $+13^{\circ}\text{C} \pm 3^{\circ}\text{C}$)
- Thermostat position: as requested either at the beginning or at the end of the heating part
- Available certifications: EC
- Produced and tested according to the EN60335 standard. Compliance with the 2014/35/EU directive
- Different insulation materials and diameters may be produced on request and after a feasibility check is performed



CAEX



*Calorflex srl declines all liability for any damage caused to persons and/or property resulting from the improper use of the product. Consult the general terms of sale and use.

CAEX

STANDARD MODELS AVAILABLE (SILICONE INSULATION)

SUPPLY VOLTAGE	15W/m	20W/m	HEATING PART MM	COLD PART MM	TOTAL LENGTH MM
220/240	30	40	2000	1000	3000
220/240	60	80	4000	1000	5000
220/240	90	120	6000	1000	7000
220/240	120	160	8000	1000	9000
220/240	150	200	10000	1000	11000
220/240	180	240	12000	1000	13000
220/240	210	280	14000	1000	15000
220/240	240	320	16000	1000	17000
220/240	270	360	18000	1000	19000
220/240	300	400	20000	1000	21000
220/240	375	500	25000	1000	26000
220/240	450	600	30000	1000	31000
220/240	525	700	35000	1000	36000
220/240	600	800	40000	1000	41000
220/240	675	900	45000	1000	46000
220/240	750	1000	50000	1000	51000
220/240	900	1200	60000	1000	61000
220/240	1050	1400	70000	1000	71000
220/240	1200	1600	80000	1000	81000
220/240	1350	1800	90000	1000	91000
220/240	1500	2000	100000	1000	101000



ELVARME



VORES PRODUKTSORTIMENT INKLUDERER:



VARMEKBAEL CFPx



VARMEKABEL STYRING



PREFORMED HEATERS



VARMEKABEL HØJTEMP. 900C



ROBUST - DEMANDING EVIROMENTS



VARMEKABLER

VI FØRER PRODUKTER INDENFOR KATEGORIERNE:



AUTOMATIK



HVAC & BYGNINGS-AUTOMATIK



KØLEPROFILER

